

MOTOR SPECIFICATION SHEET

MODEL : SF-PO 15kW 4P

USED FOR : 400V CLASS

MANUFACTURER : MITSUBISHI ELECTRIC AUTOMATION (THAILAND) CO.,LTD.

DESCRIPTION	DETAIL				
PHASE	3				
MODEL NAME	SF-PO				
RATED OUTPUT	15kW				
POLE	4				
CODE	MEATH CODE : 1M002F-401500P-NH0				
OUTLINE DRAWING NO.	ONM34O744-*				
RATED VOLTAGE (V)	380	400	415	400	
RATED FREQUENCY (Hz)	50	50	50	60	
RATED CURRENT (A)	29.5	29	29	27	
RATED SPEED (min ⁻¹)	1460	1465	1470	1760	
RATED EFFICIENCY	92.6%	92.7%	92.4%	93.2%	
EFFICIENCY CLASS	IE3				
THERMAL CLASS	130 (B)				
RATING	S1 (CONTINUOUS)				
ENCLOSURE CONSTRUCTION	TOTALLY ENCLOSED FAN COOLED				
DEGREES OF PROTECTION	IP55				
METHOD OF COOLING	IC411				
FRAME NO.	160L				
WEIGHT (kg)	136kg.				
STANDARD	JIS C 4213 / JEC-2110:2017				
INSTALLATION	FOOT MOUNTED				
ROTATION	CCW (VIEWED FROM SHAFT END)				
BEARING	LOAD SIDE : 6309ZZ				
	OPPOSITE SIDE : 6308ZZ				
BEARING GREASE	UREA GREASE				
NOISE (dB.A)*	50Hz : 70 / 60Hz : 75				
VIBRATION	V15				
CIRCUMSTANCE CONDITION	AMBIENT TEMPERATURE : -30 ~ +40°C				
	AMBIENT HUMIDITY : 100% RH (NO CONDENSATION)				
	ABOVE SEA LEVEL : 1000m OR BELOW				
	ENVIRONMENT : NO CORROSIVE/EXPLOSIVE GAS, NO STEAM OR CONDENSATION, MINIMAL DUST.				
COLOR	MUNSELL N7 (GRAY)				
TERMINAL BOX	NO. OF LEAD WIRES : 6				
	SOURCE CONNECTION : LEAD WIRES				
SHAFT SWING	≤0.05mm				
MATERIAL	FRAME : CAST IRON				
	BRACKET : CAST IRON				
	SHAFT : CARBON STEEL				
	STATOR CORE : ELECTRICAL STEEL				
	WIRE : ENAMELLED COPPER MAGNET WIRE				
	ROTOR CORE : ELECTRICAL STEEL				
	CONDUCTOR : ALUMINIUM				
	TERMINAL BOX : STEEL PLATE				
PAINTING	: ALKYD-NITROCELLULOSE RESIN				
PRODUCTION COUNTRY	THAILAND				

*Value indicates representative value, not guaranteed value.

Specifications subject to change without notice.

SPECIFICATION SHEET NO.				
SS-N-3374-A				

MODEL

SF-PO

THREE PHASE INDUCTION MOTOR

OUTLINE DRAWING

TOTALLY ENCLOSED FAN COOLED
DEGREES OF PROTECTION IP55
DUST & WATER JET PROOF

CUSTOMER

USER

FOR


CUSTOMER'S

ORDER NO.



QUANTITY

MFG.


ORDER NO.



VIEW "A"



VIEW "A"




FRAME FOOT AS VIEWED FROM BELOW

YOUR ORDER	FRAME SIZE	RATING	TH. CLASS	AMB. TEMP.	BEARINGS		COLOR	DIRECTION OF ROTATION (VIEWED FROM SHAFT END)	NO. OF LEAD WIRES	REMARK
					LOAD SIDE	OPP. SIDE				
	160L	S1 (CONT.)	130(B)	40°C	6309ZZ	6308ZZ	GRAY (MUNSELL N7)	CCW	6	

YOUR ORDER	OUTPUT		RATE VOLTAGE	IE CODE-RATE EFF.				MASS(kg)
	kW	POLE		50Hz			60Hz	
				380V	400V	415V	400V	
	15	4	380/400/415V 50Hz 400V 60Hz	IE3-92.6%	IE3-92.7%	IE3-92.4%	IE3-93.2%	-

MITSUBISHI ELECTRIC AUTOMATION (THAILAND) CO.,LTD.



DIMENSION IN mm

SCALE : NTS

OUTLINE DRAWING NO.

REV.

O N M 3 4 0 7 4 4 *